## (12) DEMANDE INTERNATIONALE PUBLIÉE EN VERTU DU TRAITÉ DE COOPÉRATION EN MATIÈRE DE BREVETS (PCT)

## (19) Organisation Mondiale de la Propriété Intellectuelle

Bureau international





(43) Date de la publication internationale 17 mars 2005 (17.03.2005)

## PCT

## (10) Numéro de publication internationale WO 2005/025089 A1

- (51) Classification internationale des brevets<sup>7</sup>: H04B 7/26, H04O 7/38
- (21) Numéro de la demande internationale :

PCT/FR2004/001696

- (22) Date de dépôt international: 30 juin 2004 (30.06.2004)
- (25) Langue de dépôt :

français

(26) Langue de publication:


français

- (30) Données relatives à la priorité : 03/10092 22 août 2003 (22.08.2003) FR
- (71) Déposant (pour tous les États désignés sauf US): ALCATEL [FR/FR]; 54, rue La Boétie, F-75008 Paris (FR).

- (72) Inventeur; et
- (75) Inventeur/Déposant (pour US seulement): MARTIN, Béatrice [FR/FR]; 84, rue Monge, F-75005 Paris (FR).
- (74) Mandataires: HEDARCHET, Stéphane etc.; Compagnie Financière Alcatel, Département Propriété Industrielle, 54 rue La Boétie, F-75008 Paris (FR).
- (81) États désignés (sauf indication contraire, pour tout titre de protection nationale disponible): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH,

[Suite sur la page suivante]

- (54) Title: METHOD OF MANAGING ACCESS TO A RANDOM-ACCESS COMMUNICATION NETWORK
- (54) Titre: GESTION DE L'ACCES A UN RESEAU DE COMMUNICATIONS A ACCES ALEATOIRE



(57) Abstract: The invention relates to a device (D) which is dedicated to the management of communications in a base station (SB) of a random-access communication network. The inventive device comprises processing means (MT) which are responsible for: (i) dividing the time intervals into slots, whereby each slot is associated with an access slot during which a terminal (UE) can transmit a network access request and whereby the width of each slot is equal to the duration of an access request; (ii) sub-dividing the time intervals into sub-intervals (SI) comprising a number of consecutive slots which is at least equal to two; (iii) in each sub-interval (SI), designating at least one invalid slot which is associated with an invalid access slot; (iv) in each sub-interval (SI), defining a number of temporally-offset windows (F) having a width equal to that of a slot, said number being at least equal to the number of slots in the sub-interval; (v) upon receipt of an access request transmitted by a calling terminal (UE), using the window (F) belonging to the access request to deduce at least one access time of the calling terminal in relation to a reference, and, subsequently, using said access time to determine the instant of transmission of an acknowledgement message to the calling terminal (UE), such that the terminal can receive the message in a pre-defined acknowledgement time interval.

[Suite sur la page suivante]

